


SRFS TELEINFRA




698-960/1710-2700MHz 6-9dBi MIMO Panel
Antenna Model: SRFS-698/2700S-9-65



ELECTRICAL SPECIFICATIONS						
Frequency Range	698-864 MHz	870-960 MHz	1710-1880MHz	1920-2170MHz	2200-2500MHz	2490-2700MHz
Polarization	±45°					
VSWR (max)	≤2.0			≤1.5		
Gain	6.5 dBi	7.0 dBi	8.5 dBi	9.0 dBi	8.0 dBi	7.5 dBi
Horizontal Beamwidth	78°	73°		65°		60°
Vertical Beamwidth	70		55/65		75/55	
Isolation	23 dB					
Input Impedence	50Ω					
Lightning Protection	DC Ground					
Max.Power	100 W			50W		
MECHANICAL SPECIFICATIONS						
Connector	2 x N-Female					
Dimensions	315x195x68 mm					
Packing Size	435x210x85 mm					
Weight	0.7 kg					
Reflector Material	ABS					
Radome Material	Brass and PCB					
Operating Temperature	-40°C to +65 °C					
Connector	Wall mount/Pole mount					
Mounting Pole	Ø38-Ø52 mm					



H-Plane



V-Plane



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 info@srfsteleinfra.in, info@srfsteleinfra.com