


SRFS TELEINFRA




**698-960/1710-2700MHz 3dBi MIMO Omni
Ceiling Antenna Model: SRFS-698/2700S-3**



ELECTRICAL SPECIFICATIONS					
Frequency Range	698-800MHz	800-960MHz	1710-2700MHz	1710-1880MHz	1880-2700MHz
Gain (Avg)	≥1.5 dBi		≥3.5 dBi	≥4 dBi	
VSWR (max)	≤1.8	≤1.5	≤1.5	≤1.8	≤1.5
Polarization	Vertical			Horizontal	
Isolation	≥26dB				
Horizontal Beamwidth	H: 360°/E: 85°/55°				
Vertical Beamwidth	H: 360°/E: 55°/45°				
Input Impedence	50Ω				
Lightning Protection	DC Ground				
Max.Power	50 W				
MECHANICAL SPECIFICATIONS					
Connector	2×N-female				
Dimensions	Ø182×123 mm				
Packing Size	170×180×180 mm				
Weight	0.37 kg				
Reflector Material	Brass				
Radome Material	ABS				
Operating Temperature	-40°C to +65 °C				



H-Plane



V-Plane



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 ✉ info@srfsteleinfra.in, info@srfsteleinfra.com