


SRFS TELEINFRA




698-960/1710-2700MHz 6/8dBi MIMO Panel
Antenna Model: SRFS-698/2700S-8-65



ELECTRICAL SPECIFICATIONS		
Frequency Range	698-960 MHz	1710-2700 MHz
Gain (Avg)	6dBi	8 dBi
VSWR (max)	≤ 2.0	≤ 1.8
Polarization	Vertical	$\pm 45^\circ$
Front to Back Ratio	≥ 26 dB	
Horizontal Beamwidth	H:65/V:55°	
Vertical Beamwidth	H:65/V:55°	
Input Impedence	50 Ω	
Lightning Protection	DC Ground	
Max.Power	50 W	
MECHANICAL SPECIFICATIONS		
Connector	2×N-Female	
Dimensions	260×170×60 mm	
Packing Size	350×260×80 mm	
Weight	0.75 kg	
Reflector Material	Aluminum	
Radome Material	ABS	
Operating Temperature	-40°C to +65 °C	
Rated Wind Velocity	210 km/h	
Mounting Pole	$\varnothing 38$ - $\varnothing 52$ mm	



H-Plane



V-Plane



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 info@srfsteleinfra.in, info@srfsteleinfra.com