SRFS TELEINFRA





SMA Female Bulkhead Right Angle Connector For P.C.B.

ELECTRICAL& MECHANICAL SPECIFICATIONS		
Frequency Range	DC-12.4GHz	
VSWR (max)	≤1.10@DC-3GHz	
Dielectric Withstanding Voltage	1000Vrms, 50Hz at sea level	
Working Voltage	335V RMS ,50Hz at sea level	
Input Impedence	50 Ω	
Contact Resistance	Center Contact ≤3mΩ Outer Contact≤2.5mΩ	
Dielectirc Resistance	≥5000MΩ	
Durability	Mating Cycles ≥500	
Material & Plating		
	Material	Plating
Body	Brass	Au
Insulator	PTFE(Teflon)	-
Center conductor	Phosphor bronze	Au
Fastening Nut	Brass	Au
Washer	Brass	Au
Ferrule Annealed	Copper	Ni
Environmental		
Temperature Range	-40°C~+85°C	
Waterproof Rate	IP 67	
RoHS	Compliant Yes	

Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in