


130-960MHz N Female 50W 3 Way Wilkinson Power Divider

Product Description:

130-960MHz N Female 50W 3 Way Wilkinson Power Divider

138-960MHz N Female Low PIM -153dBc -160dBc 3 Way Wilkinson Power Divider For Public Safety DAS IBS



Wilkinson Power Divider (WPD) is a specific class of power divider circuit that can achieve isolation between the output ports while maintaining a matched condition on all ports. The Wilkinson design can also be used as a power combiner, the high degree of isolation between the output ports prevents cross talk between the individual channels which can be easily fabricated as quarter wave lines on circuit. WPD also can be unequally divided the input power based on different usage.

Mechanical & Electrical Specifications	
Part Number	SRFS-PD-013096-ON3
Operating Frequency (MHz)	138-960
Impedance (Ohm)	50
VSWR	≤1.3
Split Loss (dB)	≤5.8
Isolation (dB)	≥18
IM3 (dBc @ 2×43dBm)	-153
Application	Indoor & Outdoor
Degree of Protection	IP65
Operating Temperature (°C)	-40 ~ + 80
Interface	N Female
Handling Power (Watt, max)	50(2w as combiner)
Peak Power (Watt, max)	200
Dimension (mm)(L×W×H, excl connector)	155 × 127.7 × 21
Net Weight (g)	830± 20
Packing Dimensions (mm,L×W×H)	210 × 170 × 65
Packing Carton Size (mm,L×W×H)	530 × 440 × 80
ROHS Compliance	Yes

Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059


+91-9027232570, +91-8800726650 ✉ info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in

SRFS TELEINFRA



130-960MHz N Female 50W 3 Way Wilkinson Power Divider



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 ✉ info@srfsteleinfra.in, info@srfsteleinfra.com

🌐 www.srfsteleinfra.in