

SRFS TELEINFRA




698-2700MHz Low PIM Indoor Panel Antenna

Model: SRFS-698/2700-7-65-ID-LP




Electrical Specifications			
Center Frequency	698-960 MHz	1710-2500 MHz	2500-2700 MHz
Gain	6.5 dBi	8 dBi	9 dB
VSWR	≤2.0	≤1.5	≤1.8
Polarization	Vertical		
PIM, 3rd Order, 2x20W	≤-150 dBc		
Horizontal Beamwidth	65°		
Vertical Beamwidth	55°		
Maximum Input Power	50W		
Input Impedance	50 Ω		
Lightning Protection	DC Ground		

Mechanical Specifications	
Connector	N-Female
Dimensions	210x180x43 mm
Packing Size	240x200x70 mm
Weight	0.5 kg
Reflector Material	Brass
Radome Material	ABS(UV Stabilized)
Rated Wind Velocity	210 km/h
Operating Temperature (°C)	-40°C to +65 °C



H-Plane



V-Plane



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in