

SRFS TELEINFRA




698-2700MHz Low PIM MIMO Indoor Dome Antenna
Model: SRFS-700/2700S-3-LP




Electrical Specifications					
Port	Port1			Port2	
Center Frequency ,MHz	698-800	800-960	1710-2700	1710-1880	1880-2700
Gain dBi	≥1.5	≥3.5		≥4	
VSWR	≤1.8	≤1.5	≤1.5	≤1.8	≤1.5
Polarization	Vertical			Horizontal	
Isolation	≥26 dB				
PIM, 3rd Order, 2x20W	≤-150 dBc				
Horizontal Beamwidth	360°				
Vertical Beamwidth	55°	45°		45°	
Maximum Input Power	50W				
Input Impedance	50 Ω				
Lightning Protection	DC Ground				

Mechanical Specifications	
Connector	2xN-Female
Dimensions	Ø182x123 mm
Packing Size	170x180x180 mm
Weight	0.37 kg
Reflector Material	Aluminum and PCB
Radome Material	ABS (UV Stabilized)
Operating Temperature (°C)	-40°C to +55 °C



H-Plane



V-Plane



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 ✉ info@srfsteleinfra.in, info@srfsteleinfra.com

🌐 www.srfsteleinfra.in