

## DC-3800MHz Rf Attenuator

### Product Description:

#### DC-3800MHz Rf Attenuator

2~5W N Male To N Female DC-3800MHz DC-6G 3db 6db 10db 15db  
20db 30db 40db Rf Attenuator

Mechanical & Electrical Specifications							
Part Number	SRFS-AT-3.8/6G-2~5W-ONX						
Operating Frequency ( MHz )	DC-3800,DC-6000						
Impedance ( Ohm )	50						
VSWR	≤1.20@DC-3800; ≤1.30@3800-6000						
Application	Indoor & Outdoor						
Degree of Protection	IP65						
Handling Power (Watt)	2~5(max)						
Interface	N Male - N Female						
Operating Temperature ( °C )	-40 ~ + 80						
Attenuation(dB)	3	5	6	10	15	20	30
Attenuation Tolerance(dB)	±0.4	±0.4	±0.5	±0.7	±0.8	±0.8	±0.8
Dimension (mm)	35×Φ18(excludes connectors)71.4×Φ18(includes connectors)						
Net Weight (g)	70						
Packing Dimensions (mm,L×W×H)	80 × 30 ×30						
Packing Carton Size (mm,L×W×H)	220 × 220 × 215						
ROHS Compliance	Yes						

Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 ✉ [info@srfsteleinfra.in](mailto:info@srfsteleinfra.in), [info@srfsteleinfra.com](mailto:info@srfsteleinfra.com)

 [www.srfsteleinfra.in](http://www.srfsteleinfra.in)

# SRFS TELEINFRA



## DC-3800MHz Rf Attenuator



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 ✉ [info@srfsteleinfra.in](mailto:info@srfsteleinfra.in), [info@srfsteleinfra.com](mailto:info@srfsteleinfra.com)

🌐 [www.srfsteleinfra.in](http://www.srfsteleinfra.in)