

SRFS TELEINFRA



FME FEMALE CRIMP CONNECTOR FOR RG 174 & LMR 100



| ELECTRICAL&MECHANICAL SPECIFICATIONS | | |
|--------------------------------------|---|---------|
| Characteristics Impedance | 50 ohm | |
| Frequency Range | DC-3GHz | |
| VSWR | 1.20:1 | |
| Working Voltage | 500 Vrms | |
| Withstand Voltage | 1000 Vrms | |
| Dielectric Withstanding Voltage | ≥2500V RMS,50Hz,at sea level | |
| Working Voltage | 1000Vrms,50 Hz at sea level | |
| Insulation Resistance | ≥5000MΩ | |
| Contact Resistance | Center Contact ≤ 1.0 mΩ Outer Contact ≤ 5 mΩ | |
| Durability | Mating cycles ≥500 | |
| MATERIAL&PLATING | | |
| | Material | Plating |
| Body | Brass | Ni |
| Insulator | PTFE | - |
| Pin/ Socket Contact | Brass / Beryllium | Au |
| Ferrule | Copper- Alloy | Ni |
| ENVIRONMENTAL SPECIFICATIONS | | |
| Temperature Range | - 55°C ~ +155 °C | |
| RoHS Compliant | Yes | |



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 ✉ info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in