



SRFS TELEINFRA



N male to N Female SRFS1830 DC~18GHz, 30W



Outline A



Outline B

Features:

- * Low VSWR
- * High Attenuation Flatness

Electrical Specifications	
Frequency	DC~18GHz
Attenuation	1-40dB
Impedance	50Ω
Average Power	30W@25°C max.
RF Connectors	N Male, N Female, SMA Male ,SMA Female
Dielectric	PEI
Tolerance	±2mm [±0.08in]
Environmental Specifications	
Operating Temperature	-55° to + 125°

Attenuation Accuracy and VSWR

Frequency(GHz)	Attenuation Accuracy (±dB) vs. Attenuation (dB)				VSWR (max.)
	1~10	11~20	21~30	31~40	
DC~4	0.4	0.5	0.6	0.7	1.2
DC~6	0.5	0.6	0.8	0.8	1.25
DC~12.4	0.6	0.7	0.8	0.9	1.35
DC~18	0.8	0.9	1.2	1.5	1.45



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in