

Wideband LPDA Antenna Model no.: SRFS- LPDA-A0033

Product Description

The LPDA-A0033 is a directional log-periodic dipole array primarily designed for EW monitoring applications. It covers the 20 to 3000 MHz with a typical gain of 6 dBi over the frequency band. The gain reduces from 6 dBi at 50 MHz to 1.5 dBi at 20 MHz. In the LPDA-A0033-01 version, the polarization is adjustable between vertical and horizontal without lowering the mast. The LPDA-A0033 version is fixed for horizontal polarization only. The antenna breaks into three for compact storage, and can be fully erected from packaging by two people in less than 10 minutes..

PRODUCT FEATURES:

- Wideband frequency coverage from 20 MHz to 3000 MHz in a single antenna
- Low VSWR
- High gain of typically 6 dBi over 90% of the band
- Easy construction of detachable elements with spring fasteners
- Compact storage as unit is easily broken into smaller parts

Electrical Specifications	
Frequency range 20 – 3000 MHz	Frequency range 20 – 3000 MHz
VSWR	<2:1 over 90% of the frequency band VSWR increases from 32 MHz - 20 MHz
Nominal input impedance	50 Ω
Connector	7/16 female
Feed power handling	1000 W CW up to 1 GHz rolling off to 250 W CW at 3 GHz
Gain	6 dBi typical, -1.5 dBi minimum (see gain graph)
Beamwidth ,E-plane	-3 dB beamwidth ≥ 60°
Beamwidth, H-Plane	-3dB at 100° typical
Polarization	Linear (vertical or horizontal)
Front-to-back ratio	≥ 12 dB, 30 – 520 MHz ≥ 6 dB, 20 – 30 MHz
Earth connection	Earth connector allowing to connect a grounding cable
Mechanical Specifications	
Dimensions (w x l)	5700 mm x 6200 mm
Material	Aluminium, stainless steel
Environmental Specifications	
Wind survival	160 km/h calculated

Wideband LPDA Antenna Model no.: SRFS- LPDA-A0033

