

# SRFS TELEINFRA



## Low Loss RA SMA Male to SMA FEMALE BULKHEAD Cable LL160 Coax



Electrical Specifications		
Frequency Range	DC-18 GHz	
Characteristic Impedance	50 ohms	
VSWR	1.33:1	
Insertion Loss(Typ.)	0.46[1.51] dB/ft[ dB/m]	
Velocity of Propagation	82.5%	
RF Shielding	-90 dB	
Capacitance	25[82.02] pF/ft[pF/m]	
CABLE		
Cable Type	LL160	
Impedence	50 Ohms	
Inner Conductor Type	Solid	
Inner Conductor Material and Plating	Copper ,Silver	
Dielectric Type	PTFE	
Number of Shields	3	
Shield Layer1	Silver Plated Copper	
Shield Layer2	Aluminum Polyester	
Shield Layer3	Silver Plated Copper Wire	
Jacket Material	FEP	
Jacket Diameter	0.16 in [4.06 mm]	
Repeated Minimum Bend Radius	0.8 in [20.32 mm]	
CONNECTORS	CONNECTOR1	CONNECTOR2
Type	SMA Male	SMA Female
Mount Method		Bulkhead
Impedance	50 Ohms	50 Ohms
Contact Material & Plating	Beryllium Copper, Gold	Beryllium Copper ,Gold
Dielectric Type	PTFE	PTFE
Outer Cond Material & Plating		Passivated Stainless Steel
Coupling Nut Material & Plating	Passivated Stainless Steel	
Body Material & Plating	Passivated Stainless Steel	Passivated Stainless Steel
Operating Range	-55 to + 165 degree C	



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 [info@srfsteleinfra.in](mailto:info@srfsteleinfra.in) [info@srfsteleinfra.com](mailto:info@srfsteleinfra.com)

[www.srfsteleinfra.in](http://www.srfsteleinfra.in)