

Medium Aviation Lights

Features:

- Current through LEDs under all conditions 80mA 20 %
- Voltage across LEDs under all conditions 2V 10 %
- Photocell auto On/Off (Internal fitted) No Extra Cost Mechanical Design
- Sealed water-proof unit conforming to IP – 65 standards
- Casing made of LM6 aluminum alloy, painted with UV paint for atmospheric protection
- UV stabilized polycarbonate lens to protect the LEDs
- Bird – Spike to keep away the droppings
- Fire retardant
- Withstands impact of up to 5J Applications:
 - High Rising Building
 - Police Communication Tower
 - Industrial Chimney



Electrical & Mechanical Specifications	
Frequency	50 - 60 Hz
Color	Signal RED
Material	Aluminium Alloy
Brand	GELTRONIX
Weight	5KG
Flashing	20 TO 40FPM
Number Of LED	720 led
Power	50watt
Operating temperature	-10 to 60 Degree C
IP Rating	IP- 65
Glass Material	Polycarbonate
Lighting Color	RED
Long life LED	1,00,000 Hours (12Hr/Day = 22 Yrs.)
Lux level	At 1 Meter 2000 Lux
Input Voltage	180 - 280V AC or 40 - 58V DC

Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 info@srfsteleinfra.com, info@srfsteleinfra.in

www.srfsteleinfra.in