

SRFS TELEINFRA



Low Loss SMA Female Bulkhead to TNC Male Cable LL160 Coax



Electrical Specifications		
Frequency Range	DC-18GHz	
Characteristic Impedance	50 ohms	
VSWR	1.33:1	
Insertion Loss(Typ.)	0.46 [1.51] dB/ft[dB/m]	
Velocity of Propagation	82.5%	
RF Shielding	-90 dB	
Capacitance	25[82.02] pF/ft[pF/m]	
CABLE		
Cable Type	LL160	
Impedance	50 Ohms	
Inner Conductor Type	Solid	
Inner Conductor Material and Plating	Copper,Silver	
Dielectric Type	PTFE	
Number of Shields	3	
Shield Layer1	Silver Plated Copper	
Shield Layer2	Aluminum Polyester	
Shield Layer3	Silver Plated Copper	
Jacket Material	FEP	
Jacket Diameter	0.16 in [4.06 mm]	
Repeated Minimum Bend Radius	0.8 in [20.32 mm]	
CONNECTORS		
	CONNECTOR1	CONNECTOR2
Type	SMA Female	TNC Male
Mount Method	Bulkhead	
Impedance	50 Ohms	50 Ohms
Contact Material & Plating	Beryllium Copper ,Gold	Beryllium Copper ,Gold
Dielectric Type	PTFE	PTFE
Body Material & Plating	Passivated Stainless Steel	Passivated Stainless Steel
Outer Cond Material & Plating	Passivated Stainless Steel	
Coupling Nut Material & Plating		Passivated Stainless Steel
Operating Range	-55to +165degree C	



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 ✉ info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in