

# SRFS TELEINFRA



## Low Loss SMA Male to RA SMA Male Cable LL160 Coax



Electrical Specifications		
Frequency Range	DC-18GHz	
Characteristic Impedance	50 ohms	
VSWR	1.35:1	
Return Loss	14.72 dB	
Insertion Loss(Typ.)	0.46 [1.51] dB/ft[ dB/m]	
Velocity of Propagation	83%	
RF Shielding	-90 dB	
Capacitance	25[82.02] pF/ft[pF/m]	
CABLE		
Cable Type	LL160	
Impedance	50 Ohms	
Inner Conductor Type	Solid	
Inner Conductor Material and Plating	Copper,Silver	
Dielectric Type	PTFE	
Number of Shields	3	
Shield Layer1	Silver Plated Copper Tape	
Shield Layer2	Aluminum Polyester	
Shield Layer3	Silver Plated Copper Wire	
Jacket Material	FEP	
Jacket Diameter	0.16 in [4.06 mm]	
Repeated Minimum Bend Radius	0.8 in [20.32mm]	
CONNECTORS	CONNECTOR1	CONNECTOR2
Type	SMA Male	SMA Male
Impedance	50 Ohms	50 Ohms
Contact Material & Plating	Beryllium Copper ,Gold	Beryllium Copper ,Gold
Dielectric Type	PTFE	PTFE
Body Material & Plating	Passivated Stainless Steel	Passivated Stainless Steel
Coupling Nut Material & Plating	Passivated Stainless Steel	Passivated Stainless Steel
Operating Range	-55to +165degree C	



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 ✉ [info@srfsteleinfra.in](mailto:info@srfsteleinfra.in), [info@srfsteleinfra.com](mailto:info@srfsteleinfra.com)

[www.srfsteleinfra.in](http://www.srfsteleinfra.in)