

SRFS-6068 Military/Police/Government/Convoy Jamming Portable RCIED Mobile Phone Pelican Jammer , Max 800W 8 Bands



Portable Briefcase RCIED ,Briefcase Jammer is a wide-band portable jamming system, designed for the protection of VIP's and groups of people from radio controlled improvised explosion by disabling the radio exploder control lines in dangerous areas and for the prevention of leakage of information through intercepting units during confidential talks. Briefcase Jammer transmits RF interference and creates a "Radio Frequency Protected Zone" around the object that prevents remote controlled bomb activation by various RF means in its vicinity with a sufficient jamming safety radius, in order to save lives and prevent serious injuries. Briefcase Jammers are also deployed to guard forces in the field, Dignitaries and VIP's, checkpoint and border crossings, roadblocks, Embassies, Police and Government offices etc. Briefcase Jammer are available in various models as per the frequency and output power. However these jammers can be customized as per the user requirements.

SRFS-6068E Europe (8 Bands)	SRFS-6068A America(8 Bands)
920-965MHz: 100W GSM 900	850-895MHz: 100W CDMA 900
1800-1880MHz 100W DCS GSM 1800	1920-1990MHz 100W PCS CDMA 1900
2100-2170MHz: 100W 3G UMTS	2100-2170MHz: 100W 3G UMTS
2620-2690MHz: 100W 4G LTE & WiMax	2500-2700MHz: 100W 4G LTE & WiMax
2400-2500MHz: 100W WiFi & Bluetooth	2400-2500MHz: 100W WiFi & Bluetooth
790-830MHz: 100W 4G Low LTE	700-800MHz: 100W 4G Low LTE
130-180MHz: 100W VHF	130-180MHz: 100W VHF
400-480MHz: 100W UHF	400-480MHz: 100W UHF
(Option) 5.0-5.5GHz:15W, 5.5-6.0GHz:15W Wi Fi 11.a Civil Remote Control Toys: 200-300MHz:100W, 300 -400MHz:100W: GPS L1 L2 L3 L4 L5: 100W	(Option) 5.0-5.5GHz:15W, 5.5-6.0GHz:15W WiFi 11.a Civil Remote Control Toys: 200-300MHz:100W, 300 -400MHz:100W: GPS L1 L2 L3 L4 L5: 100W
800 W	800 W
Power supply:	AC adapter (AC220V-DC27V or 24V/ 45 Amp) or External Battery
Jamming Range:	500-1000 meters@ -75dBm

SRFS TELEINFRA

SRFS-6068



Stand-alone modular design and individual power control.		
Adjustable Output Power each Band/Channel		
VSWR over protection for each modular.		
Working status indicator for each band modular.		
Cover network standards: AMPS,N-AMPS, DCS,NMT,TACS,GSM,CDMA,TDMA,IDEN,UMTS		
450MHz/VHF/UHF/WiFi/GPS/4G WiMax, VHF, UHF		
Designed to cut off down-link only, Therefore it doesn't have Interference to base station and repeater.		
Dimension: 626 mm(L)×49.2mm(W)× 350mm(H)		
Weight: 45 Kg (approximately) just main unit not included antenna & all accessories		
Operating temperature: -20℃ ~ +60℃		
Humidity: 5% ~ 90%		
Antennas Spec	850-960Mhz : Omni	5dBi, 650mm, 0.8Kg
	1500-1600Mhz : Omni	5dBi, 650mm, 0.8Kg
	1805-1990Mhz : Omni	5dBi, 650mm, 0.8Kg
	2000-2200Mhz : Omni	6dBi, 650mm, 0.8Kg
	2400-2500Mhz : Omni	7dBi, 650mm, 0.8Kg
	2600-2650Mhz : Omni	7dBi, 650mm, 0.8Kg
	130-180/400-500MHz: Omni	2-4 dBi, 750mm, 0.8Kg
External Battery	B-50AH 27V/50AH LiFePo4 Battery	
	Pelican Case 1440, 35kg Weight	
	Work 1-2 hours	
Warranty:	1 year	



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in

SRFS TELEINFRA

SRFS-6068



Military Antenna's Option



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in