

# SRFS TELEINFRA

## SRFS-PDK-3072 Anti-Drone Jammer



<b>PDK-3072 4 Bands</b>	
<b>Four Bands in One Directional Antenna</b>	<b>2.4-2.5GHz: 8W</b> WiFi 11.g, b, Bluetooth (Vertical Polarization)
	<b>2.4-2.5GHz: 8W</b> WiFi 11.g, b, Bluetooth ( Vertical Polarization)
	<b>GPS L1 + GLONASS L1 :10W</b> <b>1570-1620MHz</b>
	<b>5.7GHz-5.9GHz: 2.0W</b> <b>WiFi 11.a</b>
	<b>Total : 28 W</b>
<p><b>Two 2.4GHz Bands 10W per band</b>  <b>Cover Most Commercial Drones / UAVs</b>  <b>Like Dji Phantom 4, Phantom 3 Professional, Advanced, Standard series, Inspire Series...</b>  <b>Adjustable Output Power each Band/Channel, Max Output Power to 0 (OFF)</b>  <b>100% Safe VSWR over protection (Isolator) for each modular</b>  <b>Battery LED Status</b></p>	
<b>Power supply:</b>	<b>AC Charger adapter (AC220V/110V)</b>
<b>Jamming Range:</b>	<b>Radius 300-700 Meters</b>
<b>Battery Operating Time</b>	<b>80 Mins</b>
<b>Dimension: 240 x 210 x 260 mm (H x W x D)</b>	
<b>Weight: 3.6 Kg (approximately)</b>	
<b>Operating temperature: -20°C ~ +60°C</b>	



**Portable Anti-Drone Jammer**

**Max 28W, 4 Bands,**

**80 mins Built-in Battery**

**4 Bands in One Directional Antenna**



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 [info@srfsteleinfra.in](mailto:info@srfsteleinfra.in), [info@srfsteleinfra.com](mailto:info@srfsteleinfra.com)

[www.srfsteleinfra.in](http://www.srfsteleinfra.in)

# SRFS TELEINFRA

## SRFS-PDK-3072 Anti-Drone Jammer



HIGHER GAIN DIRECTIONAL ANTENNA THREE BANDS IN ONE ANTENNA

Electrical & Mechanical Specifications				
Characteristics Impedance	50 Ohm	50 Ohm	50 Ohm	50 Ohm
Frequency Range	1575-1620MHz	2400-2500MHz	2400-2500MHz	5150-5875MHz
VSWR	≤1.5	≤1.5	≤1.5	≤1.5
Gain	9dBi	13 dBi	13 dBi	16dBi
Front to Back Ratio	≥24dB	≥25dB	≥25dB	≥25dB
Polarization	Vertical	Vertical	Vertical	Vertical
Horizontal 3dB Beam Width	95°	65°	65°	25°
Vertical 3dB Beam Width	65°	50°	50°	28°
Maximum Input Power	50W	50W	50W	50W
Double 2.4GHz 10W block much longer Good Isolation each other (4 bands in)				
Lightning Protection	Direct Ground			
Connector	N-M			
Weight	0.8 kg each			
Dimensions	210*94*34mm			
Radiator Material	Alumina			
Radome Material	Black			



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 [info@srfsteleinfra.in](mailto:info@srfsteleinfra.in), [info@srfsteleinfra.com](mailto:info@srfsteleinfra.com)

[www.srfsteleinfra.in](http://www.srfsteleinfra.in)