

SRFS TELEINFRA

SRFS-PDK-3072H Anti-Drone Jammer



PDK-3072H 4 Bands	
Four Bands in One Directional Antenna	2.4-2.5GHz: 8W WiFi 11.g, b, Bluetooth (Vertical Polarization)
	2.4-2.5GHz: 8W WiFi 11.g, b, Bluetooth (Vertical Polarization) GPS L1 + GLONASS L1 :10W
	1570-1620MHz 5.6GHz-5.9GHz: 10W
	WiFi 11.a
	Total : 36 W
Two 2.4GHz Bands 10W per band	
Cover Most Commercial Drones / UAVs	
Like Dji Phantom 4 Pro V.20, Phantom 4, Phantom 3 Professional, Advanced, Standard series, Inspire Series...	
Adjustable Output Power each Band/Channel, Max Output Power to 0 (OFF)	
100% Safe VSWR over protection (Isolator) for each modular	
Battery LED Status	
Power supply:	AC Charger adapter (AC220V/110V)
Jamming Range:	Radius 500-900 Meters
Battery Operating Time	80 Mins
Dimension : 240 x 210 x 260 mm (H x W x D)	
Weight : 3.6 Kg (approximately)	
Operating temperature: -20°C ~ +60°C	



Portable Anti-Drone Jammer
Max 36W, 4 Bands, 5.8GHz 10W
80 mins Built-in Battery
4 Bands in One Directional Antenna



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in

SRFS TELEINFRA



SRFS-PDK-3072H Anti-Drone Jammer

HIGHER GAIN DIRECTIONAL ANTENNA THREE BANDS IN ONE ANTENNA

Electrical & Mechanical Specifications				
Characteristics Impedance	50 Ohm	50 Ohm	50 Ohm	50 Ohm
Frequency Range	1575-1620MHz	2400-2500MHz	2400-2500MHz	5150-5875MHz
VSWR	≤1.5	≤1.5	≤1.5	≤1.5
Gain	9dBi	13 dBi	13 dBi	16dBi
Front to Back Ratio	≥24dB	≥25dB	≥25dB	≥25dB
Polarization	Vertical	Vertical	Vertical	Vertical
Horizontal 3dB Beam Width	95°	65°	65°	25°
Vertical 3dB Beam Width	65°	50°	50°	28°
Maximum Input Power	50W	50W	50W	50W
Double 2.4GHz 10W block much longer Good Isolation each other (4 bands in)				
Lightning Protection	Direct Ground			
Connector	N-M			
Weight	0.8 kg each			
Dimensions	210*94*34mm			
Radiator Material	Alumina			
Radome Material	Black			



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in