

SRFS TELEINFRA



SRFS-PDK-3073H Drone Killer

PDK-3073H 3 Bands Pelican 1490 Case

Four Bands in One Directional Antenna	2.4-2.5GHz: 8W
	WiFi 11.g, b, Bluetooth (Vertical Polarization)
	GPS L1 + GLONASS L1 :10W
	1570-1620MHz
	5.6GHz-5.9GHz: 10W
	WiFi 11.a
	Total : 36 W
Cover Most Commercial Drones / UAVs	
Like Dji Phantom 4 Pro V.20, Phantom 4, Phantom 3 Professional, Advanced, Standard series, Inspire Series...	
Adjustable Output Power each Band/Channel, Max Output Power to 0 (OFF)	
100% Safe VSWR over protection (Isolator) for each modular	
Battery LED Status	
Power supply:	AC Charger adapter (AC220V/110V)
Jamming Range:	Radius 1000~3000 Meters
Battery Operating Time	120 Minutes
Dimension : 240 x 210 x 260 mm (H x W x D)	
Weight : 3.6 Kg (approximately)	
Operating temperature: -20°C ~ +60°C	

Pelican 1490 Case

Max 85W, 3 Bands, 5.8GHz 15W

Total 85W

1000-3000m Jamming Range



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in

SRFS TELEINFRA

SRFS-PDK-3073H Drone Killer



HIGHER GAIN DIRECTIONAL ANTENNA THREE BANDS IN ONE ANTENNA

Electrical & Mechanical Specifications			
Characteristics Impedance	50 Ohm	50 Ohm	50 Ohm
Frequency Range	1575-1620MHz	2400-2500MHz	5150-5875MHz
VSWR	≤ 1.5	≤ 1.5	≤ 1.5
Gain	8dBi	12 dBi	15dBi
Front to Back Ratio	≥ 24 dB	≥ 25 dB	≥ 25 dB
Polarization	Vertical	Vertical	Vertical
Horizontal Beam Width	65°	60°	60°
Vertical Beam Width	55°	28°	14°
Maximum Input Power	50W	50W	50W
Good Isolation each other 3 bands in)			
Lightning Protection	Direct Ground		
Connector	N-M		
Weight	1.1 kg		
Dimensions	210*94*34mm		
Radiator Material	Alumina		
Radome Material	Black		



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in