

Low Loss Flexible HLF 200 Coaxial Cable



Construction

Conductor Material	Solid Bare Copper
Stranding	1 / 1.12 mm
Dielectric	Foamed Polyethylene (FPE)
Diameter of Dielectric	2.95mm
Screen Material(1)	Bonded Aluminum Tape(100%)
Screen Material(2)	Tinned Copper wire Braid (89%)
Outer Sheath Material	Polyethylene – UV Resistant
Outer Sheath Color	Black

Electrical Characteristics

Impedance	50Ω
Cutoff Frequency	DC – 8 GHz
Velocity of Propagation	83%
Dielectric Constant	1.56
Shielding Effectiveness	>90 dB
Withstand Voltage	1.5kV
Jacket Spark	3.0kV (rms)
Capacitance	24.5 pF/ft (78.4 pF/m)
Inductance	0.061 μH/m
Conductor Resistance	≤ 17.6 Ω/Km
Outer Conductor Resistance	≤ 16.1 Ω/Km
Return loss	≥ 15 dB
Peak Power	2.5 kW

Physical Characteristics

Overall Diameter	5.0 mm
Min. Bend Radius	12.7 mm
Temperature Rating	-30°C to +85°C
Weight	30 kg /km

Drop-in replacement for

Times Microwave LMR 200

Features

- High-performance coaxial cable with durable Polyethylene jacket
- Jumper Assemblies in Wireless Communications Systems.
- Short Antenna Feeder runs.
- Any application (e.g. WLL, GPS, LMR, WLAN, WISP, WiMax, SCADA, Mobile Antennas) requiring an easily routed, low loss RF cable.

Frequency (MHz)	Attenuation	
	dB/100 ft	dB/100m
30	1.9	6.1
50	2.3	7.5
150	3.7	12.1
220	4.5	14.6
450	6.5	21.3
900	9.5	31.1
1500	12.5	40.9
1800	13.8	45.1
2000	14.6	47.8
2500	16.6	54.2

Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in