

SRFS TELEINFRA



Cluster Connector MQ4 Male For ¼" Super Flex (SRFSCONMQ4SF1/4")



| Electrical Specification | | | | |
|--------------------------------------|-------|------------------------------|------------|----------|
| Frequency Range | | DC-12GHz | | |
| Impedance | | 50Ω | | |
| Frequency | | DC-2.7GHz | 2.7-4.2GHz | 4.2-6GHz |
| VSWR | Plug | ≤1.12 | ≤1.15 | ≤1.30 |
| | Jack | ≤1.10 | ≤1.15 | ≤1.30 |
| Insertion loss | | ≤0.05vfdB | | |
| Insulation Resistance | | ≥5000MΩ | | |
| Dielectric Withstanding Voltage | | ≥1000V AC | | |
| Isolation | | ≥90dB | | |
| Environmental Specification | | | | |
| Operating& Storage Temperature Range | | -55°C to +125°C | | |
| Environmental Compliance | | RoHS | | |
| Water tightness | | IP68(1m water depth/24hours) | | |
| Salt-fog test | | ≥720h(Neutral salt spray) | | |
| Material Specification | | | | |
| Body | Brass | Ni-Sn Alloy | | |
| Center Contact | BeCu | Silver | | |
| Outer Contact | Brass | Silver | | |
| Insulator | PTFE | - | | |
| Nut | - | - | | |



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-7838349349 info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in