

SRFS TELEINFRA


4 WAY POWER SPLITTER (100-1000 MHz, 50W,N-F, IP65)



- Wide Frequency Band 100 ~ 1000 MHz
- VHF/UHF/GSM Coverage
- High Port to Port Isolation
- Low VSWR & Insertion Loss
- Application Indoor & Outdoor IP65
- Widely Used For Public Safety Communications



Electrical & Mechanical Specifications	
Model No.	SRFS-110-04-NF
Frequency (MHz)	100 ~ 1000
Input Port	Number 1
Output Port	Number 4
Split Loss(dB)	6.0
Insertion Loss(dB)	≤1.8
VSWR	≤1.35
Port Isolation(dB)	≥16
Average Power(W)	50
Impedance	50 ohm
Connector	N-Female
Color/Weight	Red painted
Temp(°C)	-35 ~ +65
Application	Indoor and outdoor IP65
Relative Humidity	5%-95%
Dimensions (mm)	225*140*22 (Connectors Excluded)



Plot no 10 Shiv Vihar A Block Najafgarh Nala Road Vikasnagar Uttam Nagar New Delhi-110059

+91-9027232570, +91-8800726650 info@srfsteleinfra.in, info@srfsteleinfra.com

www.srfsteleinfra.in