

SRFS TELEINFRA

Get connected with us:



RG 179 Coaxial Cable



Electrical specifications		
Frequency Range	3 GHz	
Velocity of Propagation, Nom.	70%	
Impedance	75 Ω	
Capacitance	64.0 pF/m	
Nominal Weight	4 kg/100m	
Bending Radius	10.16 mm	
Temperature	-55°C to +200°C	
Construction		
Item	Specification	Diameter (mm)
Dielectric	PTFE	1.6
Inner Conductor	Copper Clad Steel	0.3
Shield	Copper Braid	2.03
Conductor Type	Stranded	

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikas Nagar Uttam nagar new delhi-110059

+91 7838349349, +91 8076749052 info@srfsteleinfra.in, sales@srfsteleinfra.in, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

