

# SRFS TELEINFRA

Get connected with us:



## RG 217 Coaxial Cable



ELECTRICAL SPECIFICATIONS		
Frequency Range	4 GHz	
Min. Bending Radius	55.2 mm	
Impedance	50 $\Omega$	
Capacitance	101 pF/m	
Inductance	0.253 $\mu$ H/m	
Peak Power Rating	40 kw	
Nominal Weight	0.18 kg/m	
DC Resistance	Inner Conductor 1.77 $\Omega$ /km	
Temperature	-25° to +85°C	
Construction		
Item	Specification	Diameter (mm)
Insulation	Solid	PE
Center Conductor	Bare Copper	Wire 2.69 mm
Shield	Double Copper	Wire Braiding
Jacket Materials	PVC	Black

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.  
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.  
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.  
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

