

SRFS TELEINFRA

Get connected with us:



N Female Connector for 7/8" Feeder Cable



Electrical & Mechanical Specifications		
Frequency Range	DC-11GHz	
Characteristic Impedance	50 Ω	
VSWR	≤ 1.10	
Dielectric Withstanding Voltage	2500Vrms	
Working Voltage	2700 V max	
Contact Resistance	Inner Contact ≤ 0.4 m Ω Outer Contact ≤ 1.5 m Ω	
Insulation Resistance	≥ 10000 M Ω	
Durability	Mating cycles ≥ 500	
Material & Plating		
	Material	Plating
Body	Brass	Nickel Plated / Alloy Plated
Inner Pin	Brass	Gold Plated
Contact Resistance	Beryllium Copper	Gold Plated
Insulator	PTFE	-
Crimp Ferrule	Copper Alloy	Nickel Gold Plated
O-ring sealing	Silicone Rubber	Ni
Environmental		
Temperature Range	-40°C~+85°C	
RoHS	Compliant Yes	
Water Proof Rate	IP67	

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91-9027232570, +91-8800726650, +91 8076749052 info@srfsteleinfra.in, info@srfsteleinfra.com, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

