

Low Loss Flexible HLF 400 Coaxial Cable Tinned Copper

Features:

- High-performance coaxial cable with durable Polyethylene jacket
- Jumper Assemblies in Wireless Communications Systems.
- Short Antenna Feeder runs.
- Any application (e.g. WLL, GPS, LMR, WLAN, WISP, WiMAX, SCADA, Mobile Antennas) requiring an easily routed, low loss RF cable.



Construction	
Conductor Material	Solid Copper Clad Aluminum
Stranding	1 / 2.74 mm
Dielectric	Foamed Polyethylene (FPE)
Diameter of Dielectric	7.24 mm
Operation Frequency	DC – 8 GHz
Inner Shield	Sealed APA Tape
Outer Shield	Tinned Copper Braid
Outer Sheath Color	Black
Electrical Characteristics	
Impedance	50Ω
Cutoff Frequency	16.2 GHz
Velocity of Propagation	85%
Dielectric Constant	1.38
Shielding Effectiveness	>90 dB
Withstand Voltage	2.5kV
Jacket Spark	8.0kV (rms)
Capacitance	23.9pF/ft (78.4 pF/m)
Inductance	0.21 μH/m
Conductor Resistance	≤ 4.6 Ω/Km
Outer Conductor Resistance	≤ 5.4 Ω/Km
Return loss (30 – 2800 MHz)	≥ 15 dB
Peak Power	16.0 kW
Physical Characteristics	
Overall Diameter	10.3mm
Min. Bend Radius	24.5mm
Temperature Rating	-30°C to +85°C
Weight	10 kg /km

Frequency (MHz)	Attenuation dB/100 ft	Attenuation dB/100m
30	0.8	2.5
50	1.0	3.2
150	1.5	4.9
220	1.9	6.2
450	2.7	8.8
900	3.9	12.8
1500	5.1	16.7
1800	5.6	18.3
2000	5.9	19.3
2500	6.7	21.9

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

