

SRFS TELEINFRA

SMA Male to Male Right Angle RF Adaptor

Model No.- SRFS-SMAMM-RA-6

Get connected with us:



Electrical, Mechanical & Environmental Specification		
Impedance	50Ω	
Frequency	DC-6GHz	
Center Contact Resistance	≤3MΩ	
Outer Contact Resistance	≤2MΩ	
Insulation Resistance	≥5000mΩ	
VSWR	1.20:1	
Temperature range	-45℃ ~ +125℃	
Durability	>500 cycles	
Material & Plating		
Connector parts	Material	Plating
Body	Stainless steel	Passivated
Coupling nut	Stainless steel	Passivated
Pin Contact	Beryllium copper	Gold
Insulators	PTFE	

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91-902732570, +91-8800726650, +91 8076749052 info@srfsteleinfra.in, info@srfsteleinfra.com, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

