

SRFS TELEINFRA

SMA Male to SMA Male RF Adaptor

Model No.- SRFS-SMAMM-6

Get connected with us:



Electrical, Mechanical & Environmental Specification		
Frequency range	DC-6GHz	
Characteristic impedance	50Ω	
VSWR	1.25:1	
Durability (matings)	>500	
Temperature range	-55°C to 165°C	
RoHS Compliant	Yes	
Material & Plating		
Connector parts	Material	Plating
Pin Contact	Beryllium Copper	Gold Plated
Body	Stainless Steel (SU303)	Passivated
Insulators	PEI	

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91-902732570, +91-8800726650, +91 8076749052 info@srfsteleinfra.in, info@srfsteleinfra.com, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

