

SRFS TELEINFRA

600-4000MHz SISO Patch Panel Antennas

Get connected with us:



Part No.- SRFS-SP-0141-NF



Electrical & Mechanical Specifications					
Freq (MHz)	600-698	617-698	698-960	1710-2700	3300-4000
Gain(dBi)	5.0	5.0	6.5	7.0	9.0
VSWR	≤2.3	≤2.3	≤2.0	≤1.8	≤1.8
Front to Back Ratio(dB), dB	≥8	≥9	≥10	≥15	≥11
Horizontal Beam width	95°	100°	85°	65°	50°
Vertical Beam width	95°	90°	82°	60°	45°
Polarization	Vertical				
Impedance	50 Ω				
Max. Input Power	50 W				
Connector	N Female or Customized				
Cable	RG141				
Dimensions(mm)	180×158×60				
Weight(kg)	0.4				
Boot	Nylon				
Radom Material	ABS				
Operating Temperature	-40°C to +65 °C				
Mounting	Wall Mount Pole Mount				
PIM, 3rd Order, 2x20W(dBc)	≤-140 -150 -153				

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023



600-4000MHz SISO Patch Panel Antennas

Part No.- SRFS-SP-0141-NF

