

SRFS TELEINFRA


Get connected with us:




9 dBi Patch Panel Antenna 698-2700 MHz



Electrical Specifications		
Frequency Range	698-960 MHz	1710-2700 MHz
Gain	8dBi	9dBi
VSWR	≤1.8	≤1.5
Polarization	Vertical	
Front to Back Ratio	≥15 dB	
Horizontal Beamwidth	65°	
Vertical Beamwidth	55°	
Input Impedance	50 Ω	
Max. Power	50 W	
Lightning Protection	DC Ground	
Mechanical Specification		
Connector	N-Female	
Dimensions	210×180×43 mm	
Packing Size	240×200×70 mm	
Weight	0.5 kg	
Reflector Material	Aluminum	
Radome Material	ABS	
Operating Temperature	-40°C to +65 °C	



H-Plane



V-Plane

Add: plot no 10 shiv Vihar a block Najafgarh Sahibi river road Vikas Nagar Uttam Nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

