

SRFS TELEINFRA

Get connected with us:



Attenuator 60dB 200 W 18 GHz
Model No.- SRFS-200AT-NMNF-60-18



ELECTRICAL&MECHANICAL SPECIFICATIONS	
Characteristic Impedance	50 ohm
Frequency Range	0-18 GHz
VSWR	1.45 Max
Average	200 Watts at 25°C
Peak	1000 Watts (5 µsec pulse width)
Direction	Unidirectional, N Male input, N Female output
Temperature Range	- 55°C – +100 °C
MATERIAL&PLATING	
Body	Passivated Stainless Steel
Contacts	Gold Plated Beryllium Copper
Heat Sink	Black Anodized Aluminum
ROHS Compliant	Yes
Attenuation Accuracy(Max)	
Attenuator Value	60 dB
Accuracy	±1.4 dB

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91 7838349349 info@srfsteleinfra.in, sales@srfsteleinfra.in, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

