


### Features & Benefits

- Ultra low loss, 2.2dB/meter to 40 GHz
- Excellent phase stability with flexure 40GHz ≤6°
- Ideal for thermal vacuum applications
- Low outgassing: TML<1%, CVCM<0.1%
- All with vented connectors
- Available in armor options

### Cable Construction



No.	Construction	Size (mm)	Materials
1	Center Conductor	1.02	Solid silver-plated copper
2	Dielectric	2.80	Low density PTFE
3	Outer Conductor	3.00	Silver-plated copper tape wrap
4	Interlayer	3.24	Low density PTFE
5	Outer Shield	3.50	Silver-plated copper wire braid
6	Jacket	3.80	FEP



### Electrical

Frequency	DC-40 GHz
Impedance	50 Ω
Velocity of Propagation	82%
Shielding Effectiveness	>90 dB
Withstanding Voltage	900 V
*Mechanical Phase Stability	<±6°
Amplitude Stability vs Shaking	<±0.15dB

\* Wrapped 360° around a 38mm radius mandrel.

### Mechanical & Environmental

Min. Bending Radius Static	19mm
Min. Bending Radius Repeated	38mm
Weight	32g/m
Temperature(Operation)	-55~150 °C
Temperature(Storage)	-60~160 °C

### Attenuation(Typical@25°C&VSWR=1.0) & Power(VSWR=1.0; 40°C; Sea level)

Frequency MHz	300	1000	2000	4000	6000	8000	10000	12000	14000	18000	26500	40000
dB/100 Meter	17.3	31.9	45.5	64.9	80.1	93.1	104.7	115.3	125.1	143.0	176.1	220.5
Avg. Power kW	0.940	0.511	0.359	0.251	0.203	0.175	0.156	0.141	0.130	0.114	0.093	0.074

Attenuation at any frequency = [0.991549×SQRT(FMHz)]+[0.0005555×FMHz]

### Available connectors

Cable P/N	Connectors	Gender	Orientation	Mounting	Max Freq.(GHz)	VSWR Max
ACTV380	SMA	Male	Straight	Standard	26.5	1.3
ACTV380	SSMA	Male	Straight	Standard	18	1.3
ACTV380	2.92mm	Male	Straight	Standard	40	1.35

Other connectors available upon request.