

SRFS TELEINFRA

Surge Arrestor DC-3GHz

Part No.- SRFS-SA-3

Get connected with us:



Electrical & Mechanical Specifications

Frequency (GHz)	DC ~ 3 GHz
VSWR	2.4G ≤ 1.15 / 5.8G ≤ 1.3
Impedance	50 Ohm
Application	Outdoor
Insert loss	≤0.4dB(6.0G)
Residual voltage(1kV/μs)	< 600V
Nominal discharge voltage	230V±20%
Surge current capability	30kA once and 20kA multiple
Connector type	N-Plug/Male to N-Socket/Female
Operating Temperature (°C)	-30~+65

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91 7838349349 info@srfsteleinfra.in, sales@srfsteleinfra.in, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com

SRFS Teleinfra | All specifications are subject to change.
SRFS reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.
It may be necessary to make modifications to the part and/or the documentation of the part to implement improvements.
See www.srfsteleinfra.in for the most current information. Revised: 19 Jan 2023

