

HLF 400 Coaxial Cable Model No.- SRFS-HLF400

Features:

- High-performance coaxial cable with durable Polyethylene jacket
- Jumper Assemblies in Wireless Communications Systems.
- Short Antenna Feeder runs.
- Any application (e.g. WLL, GPS, LMR, WLAN, WISP, WiMAX, SCADA, Mobile Antennas) requiring an easily routed, low loss RF cable.



Construction	
Conductor Material	Solid Copper Clad Aluminum
Stranding	1 / 2.74 mm
Dielectric	Foamed Polyethylene (FPE)
Diameter of Dielectric	7.24 mm
Operation Frequency	DC – 8 GHz
Inner Shield	Sealed APA Tape
Outer Shield	Tinned Copper Braid
Outer Sheath Color	Black
Electrical Characteristics	
Impedance	50Ω
Cutoff Frequency	16.2 GHz
Velocity of Propagation	85%
Length	300 meter
Dielectric Constant	1.38
Shielding Effectiveness	>90 dB
Withstand Voltage	2.5kV
Jacket Spark	8.0kV (rms)
Capacitance	23.9pF/ft (78.4 pF/m)
Inductance	0.21 μH/m
Conductor Resistance	≤ 4.6 Ω/Km
Outer Conductor Resistance	≤ 5.4 Ω/Km
Return loss (30 – 2800 MHz)	≥ 15 dB
Peak Power	16.0 kW
Physical Characteristics	
Overall Diameter	10.3mm
Min. Bend Radius	24.5mm
Temperature Rating	-30°C to +85°C

Frequency (MHz)	Attenuation dB/100 ft dB/100m	
30	0.8	2.5
50	1.0	3.2
150	1.5	4.9
220	1.9	6.2
450	2.7	8.8
900	3.9	12.8
1500	5.1	16.7
1800	5.6	18.3
2000	5.9	19.3
2500	6.7	21.9

Add: plot no 10 shiv vihar a block Najafgarh Sahibi river road Vikasnagar Uttam nagar new delhi-110059

+91 84354 74330 info@srfsteleinfra.in, aayush@srfsteleinfra.in, srfsteleinfra@gmail.com

www.srfsteleinfra.in, www.srfsteleinfra.com