


086" High Density Flexible Cable Assembly, Using PS280

DC-40 GHz, Direct Solder 2.92mm Male to SMP Female **PS280-D292MSMPF-L(L:Length)**




- Length can be in meter or in inch etc, e.g, PS280-D292MSMPF-L. Standard length tolerance: $\pm 1.5\%$ or $\pm 5\text{mm}$ whichever is greater. Custom lengths and other connector types available.
- Length is measured from one connector end to the other connector end as shown above. For RA connectors, use the pin center-line.

Configuration

Connector 1	Direct solder 2.92mm male	Connector 2	SMP female
Body	Gold plated brass	Body	Gold plated BeCu
Nut	Passivated stainless steel	Center Contact	Gold plated BeCu
Center Contact	Gold plated BeCu	Cable Type	PS280

Cable Construction



No.	Construction	Size (mm)	Materials
1	Center Conductor	0.51	Silver plated copper
2	Dielectric	1.63	Solid PTFE
3	Outer Conductor	1.79	Silver plated copper tape wrap
4	Outer Shield	2.16	Silver plated copper wire braid
5	Jacket	2.80	FEP



Electrical

Frequency	DC-40 GHz
Impedance	50 Ω
*VSWR Max	1.4-1.45
*IL Max(0.1 meter assembly)	1.2dB
Velocity of Propagation	70%

Mechanical & Environmental

Min.Bending Radius Static	14mm
Min. Bending Radius Repeated	28mm
Temperature(Operation)	-50~105 $^{\circ}\text{C}$
Temperature(Storage)	-60~105 $^{\circ}\text{C}$

* The VSWR and IL include the loss and reflection contributions from the SMP adapters used during testing.



086" High Density Flexible Cable Assembly, Using PS280

DC-40 GHz, Direct Solder 2.92mm Male to SMP Female **PS280-D292MSMPF-L(L:Length)**

Bulk Cable Attenuation(Typical@25°C) & Power(VSWR=1.0; 40°C; Sea level)

Frequency MHz	300	1000	2000	4000	6000	8000	10000	12000	14000	18000	26500	40000
dB/100 Meter	37.0	69.3	100.3	146.5	183.7	216.4	246.1	273.7	299.7	348.2	440.8	570.9
Avg.Power kW	0.187	0.100	0.069	0.047	0.038	0.032	0.028	0.025	0.023	0.020	0.016	0.012
Attenuation at any frequency= $[2.066929 \times \text{SQRT}(\text{FMHz})] + [0.003937 \times \text{FMHz}]$												